Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nedis

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: CLCC700

Type of light source:

| Lighting technology used: | LED | Non-directional or directional: | NDLS |
|-------------------------------|----------------|---------------------------------|------|
| Light source cap-type | other elec- | | |
| (or other electric interface) | tric interface | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | No |

Product parameters

| Parameter | | Value | Parameter | Value | | | |
|--------------------------------------------------------------------|---------------------------------------------------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--|--|--|
| General product parameters: | | | | | | | |
| Energy consum mode (kWh/10 up to the neares | | 4 | Energy efficiency class | G | | | |
| dicating if it refe a sphere (360°) | s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º) | 290 in Sphere (360°) | Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set | 2 500 | | | |
| On-mode pow pressed in W | ver (P _{on}), ex- | 3,6 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | | | |
| (P _{net}) for CLS, e | andby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 89 | | | |
| Outer dimen- | Height | 5 | Spectral power dis- | See image | | | |
| sions without separate con- trol gear, light- ing control | Width Depth | 65 17 000 | tribution in the range 250 nm to 800 nm, at full-load | in last page | | | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | | | | |
|----------------------------------------------------------------------------|------|------------------------------|-------|--|--|--|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordi- | 0,485 | | | |
| | | nates (x and y) | 0,427 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 | | | |
| the lumen maintenance factor | 0,90 | | | | | |

(a)'-' : not applicable;

(b)_{'-'} : not applicable;

