## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or tra	ide mark:	Nedis
------------------------	-----------	-------

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: CLCS768

Type of light source	Type	of light	source:
----------------------	------	----------	---------

Lighting technology used:	LFD	Non-directional or	NDLS
Lighting teermology used:		directional:	. 175 23
Light source cap-type	other elec-		
(or other electric interface)	tric interface		
Mains or non-mains:	NMLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No
Product parameters			
Parameter	Value	Parameter	Value

Parameter		Value	Parameter	Value
	General product parameters:			
Energy consur mode (kWh/10 up to the neare	00 h), rounded	8	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	790 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	7,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	81
Outer dimen-	Height	5	Spectral power dis-	See image
sions without	Width	80	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	8 600	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,485
		nates (x and y)	0,427
Parameters for LED and OLED light sources:			
R9 colour rendering index value	0	Survival factor	0,90
the lumen maintenance factor	0,90		

(a)'-': not applicable; (b)'-': not applicable;

