Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name or t | trade mark: | Nedis |
|----------------------|-------------|-------|
|----------------------|-------------|-------|

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: CLLS180

| _ | • | | | |
|------|-----|--------|------|-----|
| Tyna | Ot. | lioht | sour | CD. |
| IVDC | O. | IIGIIL | 30ui | LC. |

| Drodust narameters | | | |
|---|-------------------------------|---------------------------------|------|
| Anti-glare shield: | No | Dimmable: | No |
| High luminance light source: | No | | |
| Colour-tuneable light source: | No | Envelope: | - |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Light source cap-type (or other electric interface) | other elec- tric interface | | |
| Lighting technology used: | LED | Non-directional or directional: | NDLS |

Product parameters

| Product parameters | | | | |
|---|---|-------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| General product parameters: | | | | |
| Energy consummode (kWh/10) up to the neares | 00 h), rounded | 4 | Energy efficiency class | F |
| dicating if it refe a sphere (360°), | s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º) | 360 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 500 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 3,1 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | andby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 82 |
| Outer dimen- | Height | 5 | Spectral power dis- | See image |
| sions without | Width | 30 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 16 500 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | |
|--|------|------------------------------|-------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordi- | 0,485 |
| | | nates (x and y) | 0,427 |
| Parameters for LED and OLED light sources: | | | |
| R9 colour rendering index value | 0 | Survival factor | 0,90 |
| the lumen maintenance factor | 0,90 | | |

(a)'-': not applicable; (b)'-': not applicable;

