## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Nedis

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

## Model identifier: LBFE27G452

## Type of light source:

|     | directional:                  |  |
|-----|-------------------------------|--|
| E27 |                               |  |
|     |                               |  |
| MLS | Connected light source (CLS): | No   |
| No  | Envelope:                     | -  |
| No  |                               |  |
| No  | Dimmable:                     | No   |
| -   | MLS<br>No<br>No<br>No         | MLS Connected light<br>source (CLS):<br>No Envelope:<br>No |

| Product parameters  |                                   |                         |  |              |  |  |
|---|-----------------------------------|-------------------------|--|--------------|--|--|
| Parameter   |                                   | Value                   | Parameter  | Value        |  |  |
| General product parameters:   |                                   |                         |  |              |  |  |
| Energy consum<br>mode (kWh/100<br>up to the neares                              | 00 h), rounded                    | 5                       | Energy efficiency<br>class   | F            |  |  |
| Useful luminous<br>dicating if it refe<br>a sphere (360º),<br>(120º) or in a na | ers to the flux in in a wide cone | 470 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the near-<br>est 100 K, or the<br>range of correlat-<br>ed colour temper-<br>atures, rounded to<br>the nearest 100 K,<br>that can be set | 2 700        |  |  |
| On-mode pow<br>pressed in W   | rer (P <sub>on</sub> ), ex-       | 4,5                     | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| Networked st<br>(P <sub>net</sub> ) for CLS, e<br>and rounded to<br>imal        | •                                 | -                       | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 80           |  |  |
| Outer dimen-  | Height                            | 75                      | Spectral power dis-  | See image    |  |  |
| sions without<br>separate con-<br>trol gear, light-<br>ing control              | Width<br>Depth                    | 45<br>45                | tribution in the<br>range 250 nm to 800<br>nm, at full-load  | in last page |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre)   |                     |  |                |
|--|---------------------|--|----------------|
| Claim of equivalent power <sup>(a)</sup>   | Yes                 | lf yes, equivalent power (W)             | 40             |
|  |                     | Chromaticity coordi-<br>nates (x and y)  | 0,463<br>0,420 |
| Parameters for LED and OLED lig  | sht sources:        |  |                |
| R9 colour rendering index value  | 0                   | Survival factor                          | 0,90           |
| the lumen maintenance factor   | 0,93                |  |                |
| Parameters for LED and OLED m  | ains light sources: |  |                |
| displacement factor (cos φ1)   | 0,50                | Colour consistency<br>in McAdam ellipses | 6              |
| Claims that an LED light source<br>replaces a fluorescent light<br>source without integrated bal-<br>last of a particular wattage. | _(b)                | If yes then replace-<br>ment claim (W)   | -              |
| Flicker metric (Pst LM)  | 1,0                 | Stroboscopic effect<br>metric (SVM)      | 0,9            |

(a)<sub>'-'</sub> : not applicable;

(b)'\_-' : not applicable;

