

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Nedis

**Supplier's address:** Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

**Model identifier:** LTLGQ3M2WT

## Type of light source:

|                                                     |     |                                 |     |
|-----------------------------------------------------|-----|---------------------------------|-----|
| Lighting technology used:                           | LED | Non-directional or directional: | DLS |
| Light source cap-type (or other electric interface) | /   |                                 |     |
| Mains or non-mains:                                 | MLS | Connected light source (CLS):   | No  |
| Colour-tuneable light source:                       | Yes | Envelope:                       | -   |
| High luminance light source:                        | No  |                                 |     |
| Anti-glare shield:                                  | No  | Dimmable:                       | Yes |

## Product parameters

| Parameter                                                                                                                                      | Value                   | Parameter                                                                                                                                                  | Value                  |
|------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| <b>General product parameters:</b>                                                                                                             |                         |                                                                                                                                                            |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer                                                                  | 5                       | Energy efficiency class                                                                                                                                    | G                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 260 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 or 6 500         |
| On-mode power ( $P_{on}$ ), expressed in W                                                                                                     | 4,8                     | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal                                                                               | 0,50                   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal                                                | -                       | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 90                     |
| Outer dimensions without separate control gear, lighting control                                                                               | Height                  | Spectral power distribution in the range 250 nm to 800 nm, at full-load                                                                                    | See image in last page |
|                                                                                                                                                | Width                   |                                                                                                                                                            |                        |
|                                                                                                                                                | Depth                   |                                                                                                                                                            |                        |

|                                                                                                                         |      |                                                                    |                |  |
|-------------------------------------------------------------------------------------------------------------------------|------|--------------------------------------------------------------------|----------------|--|
| parts and non-lighting control parts, if any (millimetre)                                                               |      |                                                                    |                |  |
| Claim of equivalent power <sup>(a)</sup>                                                                                | -    | If yes, equivalent power (W)                                       | -              |  |
|                                                                                                                         |      | Chromaticity coordinates (x and y)                                 | 0,381<br>0,371 |  |
| <b>Parameters for directional light sources:</b>                                                                        |      |                                                                    |                |  |
| Peak luminous intensity (cd)                                                                                            | 135  | Beam angle in degrees, or the range of beam angles that can be set | 118            |  |
| <b>Parameters for LED and OLED light sources:</b>                                                                       |      |                                                                    |                |  |
| R9 colour rendering index value                                                                                         | 82   | Survival factor                                                    | 1,00           |  |
| the lumen maintenance factor                                                                                            | 0,95 |                                                                    |                |  |
| <b>Parameters for LED and OLED mains light sources:</b>                                                                 |      |                                                                    |                |  |
| displacement factor (cos $\phi_1$ )                                                                                     | 1,00 | Colour consistency in McAdam ellipses                              | 5              |  |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | -(b) | If yes then replacement claim (W)                                  | -              |  |
| Flicker metric (Pst LM)                                                                                                 | 0,2  | Stroboscopic effect metric (SVM)                                   | 0,0            |  |

(a) '-': not applicable;

(b) '-': not applicable;

