Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nedis

Supplier's address: -

Model identifier: WIFICOL20BK

Type of light source:

ing control

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	-					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Yes			
Product parameters						

Parameter		Value	Parameter	Value	
General product parameters:					
• ·	nption in on- 00 h), rounded st integer	12	Energy efficiency class		
dicating if it refe a sphere (360º) (120º) or in a na	s flux (фuse), in- ers to the flux in , in a wide cone nrow cone (90º)	1 000 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	3 200	
On-mode pow pressed in W	ver (P _{on}), ex-	-	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	-	
(P _{net}) for CLS, e	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set		
Outer dimen-	Height	260	Spectral power dis-	See image	
sions without	Width	73	tribution in the	in last page	
separate con- trol gear, light-	Depth	131	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	lf yes, equivalent power (W)	-			
		Chromaticity coordi- nates (x and y)	-			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-			
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	_	Stroboscopic effect metric (SVM)	-			

(a)_{'-'} : not applicable;

(b)'_-' : not applicable;