## **Product Information Sheet**

(P<sub>net</sub>) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources									
Supplier's name or trade mark: Nedis Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL Model identifier: WIFILC10WTE14									
						Type of light source:			
						Lighting technology used:	LED	Non-directional or directional:	-
Light source cap-type	-								
(or other electric interface)									
Mains or non-mains:	-	Connected light source (CLS):	No						
Colour-tuneable light source:	No	Envelope:	-						
High luminance light source:	No								
Anti-glare shield:	No	Dimmable:	-						
	Product par	rameters							
Parameter	Value	Parameter	Value						
	General product	parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	5	Energy efficiency class	G						
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	350 in -	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	-						
On-mode power (P <sub>on</sub> ), expressed in W	4,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	-						
Networked standby power	-	Colour rendering in-							

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set

tribution

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	-	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-	Survival factor	-	
the lumen maintenance factor	-			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;