Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: WIFILF10WTG125

Type	of I	light	source	е:
IVE	U I I	115111	30410	

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Froduct parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
Energy consummode (kWh/10 up to the neares	00 h), rounded	5	Energy efficiency class	F	
dicating if it refe a sphere (360°),	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700	
On-mode pow pressed in W	ver (P _{on}), ex-	5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimensions without	Height Width	175 125	Spectral power distribution in the	See image in last page	
separate con- trol gear, light- ing control	Depth	125	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	60			
		Chromaticity coordinates (x and y)	0,457 0,410			
Parameters for LED and OLED light sources:						
R9 colour rendering index valu	e 0	Survival factor	0,90			
the lumen maintenance factor	0,94					
Parameters for LED and OLED	Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated balast of a particular wattage.	nt	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9			

(a)'-': not applicable; (b)'-': not applicable;

