

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Nedis

**Supplier's address:** -

**Model identifier:** WIFILS51CRGB

**Type of light source:**

|   |     |                                 |      |
|---|-----|---------------------------------|------|
| Lighting technology used:                           | LED | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | -   |                                 |      |
| Mains or non-mains:                                 | -   | Connected light source (CLS):   | Yes  |
| Colour-tuneable light source:                       | Yes | Envelope:                       | -    |
| High luminance light source:                        | No  |                                 |      |
| Anti-glare shield:                                  | No  | Dimmable:                       | -    |

## Product parameters

| Parameter  | Value    | Parameter  | Value                  |
|--|----------|--|------------------------|
| <b>General product parameters:</b>   |          |  |                        |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 24       | Energy efficiency class  | F                      |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 900 in - | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | -                      |
| On-mode power ( $P_{on}$ ), expressed in W   | -        | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | -                      |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -        | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | -...-                  |
| Outer dimensions without separate control gear, lighting control   | Height   | Spectral power distribution in the range 250 nm to 800 nm, at full-load  | See image in last page |
|  | Width    |  |                        |
|  | Depth    |  |                        |

|   |   |                                    |        |  |
|---|---|------------------------------------|--------|--|
| parts and non-lighting control parts, if any (millimetre) |   |                                    |        |  |
| Claim of equivalent power <sup>(a)</sup>                  | - | If yes, equivalent power (W)       | -      |  |
|   |   | Chromaticity coordinates (x and y) | -<br>- |  |
| <b>Parameters for LED and OLED light sources:</b>         |   |                                    |        |  |
| R9 colour rendering index value                           | - | Survival factor                    | -      |  |
| the lumen maintenance factor                              | - |                                    |        |  |

(a) - : not applicable;

(b) - : not applicable;