Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Nedis

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: WIFILSC20CWT

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	N.A					
(or other electric interface)						
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes			
Colour-tuneable light source:	Yes	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	No			
Product parameters						

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neares		10	Energy efficiency class	F		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	1 000 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	27006500		
On-mode pow pressed in W	ver (P _{on}), ex-	10,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50		
(P _{net}) for CLS, e	andby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	90		
Outer dimen- sions without separate con- trol gear, light- ing control	Height	2	Spectral power dis- tribution in the range 250 nm to 800 nm, at full-load	See image		
	Width	10		in last page		
	Depth	2 000		Dago 1 / 3		

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,460			
		nates (x and y)	0,420			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	1	Survival factor	0,90			
the lumen maintenance factor	0,95					

(a)'-' : not applicable;

(b)_{'-'} : not applicable;

