Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name	e or trad	le mark:	Nedis
-----------------	-----------	----------	-------

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: WIFILXC01W200

_	•			
Tyna	Ot.	lioht	sour	CD.
IVDC	O.	IIGIIL	30ui	LC.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	N/A		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
_ ·	nption in on- 00 h), rounded st integer	4	Energy efficiency class	G	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	345 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500	
On-mode pow pressed in W	ver (P _{on}), ex-	3,9	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50	
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	69	
Outer dimensions without separate control gear, lighting control	Height	30	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image	
	Width	5		in last page	
	Depth	3 000			

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,485
		nates (x and y)	0,426
Parameters for LED and OLED light sources:			
R9 colour rendering index value	-14	Survival factor	0,90
the lumen maintenance factor	0,90		

(a)'-': not applicable; (b)'-': not applicable;

