Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Ne	dis
-----------------------------------	-----

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: WIFILXC02W200

_	•			
Typa	Λt	liaht	source:	
IVDE	VI.	IIGIIL	source.	

High luminance light source: No Anti-glare shield: No	Envelope: - Dimmable: Yes
nign iuminance light source:	Envelope
High luminance light course. No	Envelope
Colour-tuneable light source: No	Envolonos
Mains or non-mains: NMLS	Connected light Yes source (CLS):
(or other electric interface)	
Light source cap-type N/A	
Lighting technology used: LED	Non-directional or NDLS directional:

Product parameters							
Parameter	arameter		Parameter	Value			
General product parameters:							
Energy consummode (kWh/10) up to the neares	00 h), rounded	4	Energy efficiency class	G			
dicating if it refe a sphere (360°),	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500 or 9 000			
On-mode power (P _{on}), ex- pressed in W		4,5	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,50			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	77			
Outer dimen-	Height	30	Spectral power dis-	See image			
sions without	Width	5	tribution in the	in last page			
separate con- trol gear, light- ing control	Depth	3 000	range 250 nm to 800 nm, at full-load				

parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,370	
		nates (x and y)	0,426	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	-14	Survival factor	0,90	
the lumen maintenance factor	0,90			

(a)'-': not applicable; (b)'-': not applicable;

