## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Nedis B.V., De Tweeling 28, 5215 MC 's-Hertogenbosch Noord-Brabant, NL

Model identifier: WIFILXC04W250

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	N/A				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Due de est us aus us atsus					

## **Product parameters**

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	4	Energy efficiency class	G		
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	305 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500 or 9 000		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	3,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,50		
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	0,50	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	77		
Outer dimen-	Height	30	Spectral power dis-	See image		
sions without	Width	5	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	5 000	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,371 0,358			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-1	Survival factor	0,90			
the lumen maintenance factor	0,90					

(a)'-': not applicable; (b)'-': not applicable;

